



DIMENSIONAL TOLERANCE TABLE	
DIVISION	TOLERANCE
Less than 4.0	±0.3
4.0~16.0	±0.5
16.0~63.0	±0.7
63.0~250.0	±1.2
250.0~1000.0	±2.0

UNIT : mm

※2

※1: SPCC, etc (COVER PART, COLOR: IVORY)

RoHS Compliant [Cd ≤75ppm]	
REMARKS	BRASS: Cd ≤75ppm PHOSPHOR BRONZE: Pb <4wt%

7						SCALE	1/1	DRAWN	INSPECTED	APPROVED	CHECKED	PART NUMBER
6						TOLERANCE	※2	上	檜	山	三	BNC-0092
5						UNIT	mm	'24,04,24	'24,04,24	'24,04,24	'24,04,24	
4						DATE	2024.04.24	領	澤	本	村	
3								PROJECTION		株式会社 トーコン TO-CONN CO., LTD.		DRAWING NO. W-0396402
2	LABEL	-----	1	--								
1	BNC-J TYPE COAXIAL 2 DISTRIBUTOR	※1	1	--	BODY/Ni. CENTER PIN/Ag							
NO.	DESCRIPTION	MATERIAL	Q'TY	FINISH	REMARK							

# PRODUCT SPECIFICATIONS

Part number: BNC-0092

No. 0392584

Drawing number: W-0396402

Nominal 1 Standard JIS C 5412  
 2 Power handling 250mW  
 3 Rated frequency 40MHz~900MHz  
 4 Impedance 50Ω(unbalance)  
 5 Operating temperature 0°C~+50°C、  
 and humidity range 30~90%RH※No condensation  
 6 Storage temperature -20°C~+70°C、  
 and humidity range 30~90%RH ※No condensation



		Test Items	Test Method/Value	Remarks
1	E L E C T R I C A L	Frequency characteristic	40MHz~900MHz: 1.0dB(Max.)	
2		Isolation	40MHz~900MHz: 20dB(Min.)	
3		VSWR	40MHz~900MHz: 1.3(Max.)	
4		Insertion loss	40MHz~900MHz: 4.0dB(Max.)	
5	M E C H A N I C A L	Compatibility	No defects or abnormalities	Connecting with a standard-compliant connector
6				
7				
8				
9				
10		O T H E R S		
11				

※The structural shape is shown in the attached drawing (Drawing number:W-0396402)

	REVISIONS	DATE
1		
2		
3		

Checked	Approved	Inspected	Prepared
 24.04.24 村	 24.04.24 山本	 24.04.24 水澤	 24.04.24 上原

GKQM-24