



DIMENSIONAL TOLERANCE TABLE	
TOLERANCE	DIVISION
Less than 4.0	±0.3
4.0~16.0	±0.5
16.0~63.0	±0.7
63.0~250.0	±1.2
250.0~1000.0	±2.0

SCALE : mm
*2

*1: SPCC, etc (COVER PART, COLOR: IVORY)

RoHS Compliant $Cd \leq 75ppm$	
REMARKS	BRASS: $Cd \leq 75ppm$ PHOSPHOR BRONZE: $Pb < 4wt\%$

7						SCALE	1/1	DRAWN	INSPECTED	APPROVED	CHECKED	PART NUMBER
6						TOLERANCE	*2	井	檜	山	三	BNC-0094C
5						UNIT	mm	'24.04.15	'24.04.15	'24.04.15	'24.04.15	
4								出	澤	本	村	
3												
2	LABEL	-----	1	--								
1	BNC75Ω-J TYPE COAXIAL 4 DISTRIBUTOR	*1	1	--	BODY/Ni, CENTER PIN/Aq	DATE	2024.04.15	PROJECTION				DRAWING NO. U-0396562
NO.	DESCRIPTION	MATERIAL	Q'TY	FINISH	REMARK							

PRODUCT SPECIFICATIONS

Part number: BNC-0094C

No. 0392676

Drawing number: U-0396562

Nominal	1 Standard	JEITA RC 5233
	2 Power handling	250mW
	3 Rated frequency	40MHz~900MHz
	4 Impedance	75Ω(unbalance)
	5 Operating temperature and humidity range	0°C~+50°C、 30~90%RH※No condensation
	6 Storage temperature and humidity range	-20°C~+70°C、 30~90%RH ※No condensation



	Test Items	Test Method/Value	Remarks
1	E L E C T R I C A L	Frequency characteristic	40MHz~900MHz: 2.0dB(Max.)
2		Isolation	40MHz~900MHz: 20dB(Min.)
3		VSWR	40MHz~900MHz: 1.5(Max.)
4		Insertion loss	40MHz~900MHz: 8.0dB(Max.)
5	M E C H A N I C A L	Compatibility	No defects or abnormalities
	O T H E R S		

※The structural shape is shown in the attached drawing (Drawing number:U-0396562)

	REVISIONS	DATE
1		
2		
3		

Checked	Approved	Inspected	Prepared
 24.04.15	 24.04.15	 24.04.15	 24.04.15

GKQM-24