

PRODUCT SPECIFICATIONS

Part No. BNCP-174A

No. 0311692

DWG No. X-0314535

Nominal 1 Standard JIS C 5412
2 Voltage rating AC 500V
3 Impedance 50Ω
4 [OPR] Temp-Range -40℃~+85℃



Test Items		Procedures/Test method	Requirements
1	DESIGN	Design & construction	Specified on relevant product drawing (DWG No. X-0314535) No defects or abnormalities
2		Materials	
3		Finishes	
4	ELECTRICAL	Insulation Resistance	DC 500V 1000MΩ (Min.)
5		Withstanding voltage	AC 1000V (1 minute.) No defects or abnormalities
6		Contact resistance	The method of which, the voltage drop of the contact duration should not exceed 1-kHz AC or 1mV DC 3mΩ (Max.)
7		V. S. W. R	DC~500MHz 1.3 (Max.)
8	MECHANICAL	Compatibility	Connecting with a standard-compliant connector No defects or abnormalities
9		Cable tensile strength	At axial tensile force 49N (Min.) No defects or abnormalities
10		Tensile strength of coupling mechanism	At axial tensile force 245N No defects or abnormalities
11		Cable group	RG-174/U、RG-188A/U、RG-316/U

	Remarks	Date
1	Withstanding voltage AC 750 → AC 1000	2024/7/24
2		
3		

Checked	Approved	Inspected	Prepared
三 24.07.24 村	山 24.07.24 本	石 24.07.24 川	檜 24.07.24 澤

GKQM-25