



RoHS Compliant

7						尺 5 / 1	製 図	検 図	承 認	確 認	品 名
6	圧着スリーブ	黄銅	1	Au			井	檜	山	三	MMCX-P-316
5	中心コンタクト	黄銅	1	Au			'23,12,23	'23,12,23	'23,12,23	'23,12,23	
4	横棒	黄銅	1	Au			出	澤	本	村	
3	Cリング	ベリリウム銅	1	Au		単 位 mm					
2	絶縁体	テフロン	1	--		日 付 2016.03.04					
1	本体	黄銅	1	Au		投 影 法	◎	◁	Logo	株式会社 トーコネ TO-CONNE CO.,LTD.	図 番 Y-1014725
番号	部 品 名	材 質	数 量	処 理	備 考						

PRODUCT SPECIFICATIONS

Part No. MMCX-P-316
 DWG No. Y-1014725
 Nominal 1 Frequency range 6 GHz
 2 Impedance 50 Ω

No. 1011776
 To-Conne Co., Ltd. (TYO)

Checked	Inspected	Prepared
山 16.04.25 本	檜 16.04.25 澤	栗 16.04.25 原

		Test Items	Procedures/Test method	Requirements
1	DESIGN	Design & construction	Specified on relevant product drawing (DWG No. Y-1014725)	No defects or abnormalities
2		Materials		
3		Finishes		
4	ELECTRICAL	Insulation Resistance	DC 500V	1000MΩ (Min.)
5		Withstanding voltage	DC 500V (1 minute.)	No defects or abnormalities
6		Contact resistance	DC 0.2V、 1A	Inner 5mΩ (Max.) Outer 2.5mΩ (Max.)
7		V. S. W. R	0~6.0GHz	1.3 (Max.)
8	MECHANICAL	Compatibility	Connecting with a standard-compliant connector	No defects or abnormalities
9		Force to engage/disengage	Force to engage 6.3N (Min.) 36N (Max.) Force to disengage 6.3N (Min.) 36N (Max.)	No defects or abnormalities
10		Cable tensile strength	At axial tensile force 44.48N (Min.)	No defects or abnormalities
11		Cable group	RG-316/U	

GKQM-19-1

	Remarks	Date
1	V. S. W. R 3.0GHz 1.35 (Max.) → 6.0GHz 1.3 (Max.) 変更	2016.04.25
2		
3		