



DIMENSIONAL TOLERANCE TABLE	
TOLERANCE	DIVISION
Less than 4.0	±0.3
4.0~16.0	±0.5
16.0~63.0	±0.7
63.0~250.0	±1.2
250.0~1000.0	±2.0

SCALE : mm
*2

RoHS Compliant [Cd ≤75ppm]

REMARKS BRASS: Cd ≤75ppm
PHOSPHOR BRONZE: Pb <4wt%

*1: A5052P, etc (COVER PART, COLOR: IVORY)

7						SCALE	1/1	DRAWN	INSPECTED	APPROVED	CHECKED	PART NUMBER
6						TOLERANCE	*2	井	檜	山	三	
5						UNIT	mm	'24.04.16	'24.04.16	'24.04.16	'24.04.16	
4								出	澤	本	村	
3												
2	LABEL	-----	1	--								
1	N-J TYPE COAXIAL 2 DISTRIBUTOR	*1	1	--	BODY/Ni, CENTER PIN/Aq	DATE	2024.04.16	PROJECTION				DRAWING NO. U-0596564
NO.	DESCRIPTION	MATERIAL	Q'TY	FINISH	REMARK							

PRODUCT SPECIFICATIONS

Part number: N-9182

No. 0592678

Drawing number: U-0596564

Nominal 1 Standard	JIS C 5411
2 Power handling	250mW
3 Rated frequency	900MHz~1800MHz
4 Impedance	50Ω(unbalance)
5 Operating temprure range	-10°C~+50°C



		Test Items	Test Method/Value	Remarks
1	E L E C T R I C A L	Isolation	900MHz~1800MHz: 20dB(Min.)	
2		VSWR	900MHz~1800MHz: 1.3(Max.)	
3		Insertion loss	900MHz~1800MHz: 3.5dB(Max.)	
4	M E C H A N I C A L	Compatibility	No defects or abnormalities	Connecting with a standard-compliant connector
	O T H E R S			

※The structural shape is shown in the attached drawing (Drawing number:U-0596564)

	REVISIONS	DATE
1		
2		
3		

Checked	Approved	Inspected	Prepared
三 24.04.16 村	山 24.04.16 本	檜 24.04.16 澤	井 24.04.16 出

GKQM-24