

PRODUCT SPECIFICATIONS

Part No. NPJ50AT6G40W-20dB

No. 0592481

DWG No. W-0596216

Nominal 1 Standard JIS C 5411
 2 Power handling 40W
 3 Frequency range 6GHz
 4 Impedance 50Ω
 5 [OPR]Temp-Range -45°C~+85°C



株式会社 トーコネ
 TO-CONNE CO.,LTD.

	Test Items	Procedures/Test method	Requirements
1	DESIGN	Design & construction	Specified on relevant product drawing (DWG No. W-0596216) No defects or abnormalities
2		Materials	
3		Finishes	
4	ELECTRICAL	Attenuation	DC~6GHz 20±1.1dB
5		V. S. W. R	DC~3GHz 3~6GHz 1.2(Max.) 1.3(Max.)
6	MECHANICAL	Compatibility	Connecting with a standard-compliant connector No defects or abnormalities
7		Tensile strength of coupling mechanism	At axial tensile force 300N No defects or abnormalities
8		Connection nut tightening torque	0.9~1.7N·m
	ENVIRONMENTAL		
9		Waterproof	IPX7 No water ingress inside the connector

	Remarks	Date
1		
2		
3		

Checked	Approved	Inspected	Prepared
三 23.01.12 村	山 23.01.12 本	檜 23.01.12 澤	渡邊 23.01.12 直弘

GKQM-25