

PRODUCT SPECIFICATIONS

Part No. NPJ50AT6G50W-30dB

No. 0592415

DWG No. W-0596075

Nominal 1 Standard JIS C 5411
2 Power handling 50W
3 Frequency range 6GHz
4 Impedance 50Ω
5 [OPR]Temp-Range -45°C~+85°C



株式会社 トーコネ
TO-CONNE CO.,LTD.

	Test Items	Procedures/Test method	Requirements
1	DESIGN	Design & construction	Specified on relevant product drawing (DWG No. W-0596075) No defects or abnormalities
2		Materials	
3		Finishes	
4	ELECTRICAL	Attenuation	DC~6GHz 30±1.4dB
5		V. S. W. R	DC~3GHz 3~6GHz 1.2(Max.) 1.3(Max.)
6	MECHANICAL	Compatibility	Connecting with a standard-compliant connector No defects or abnormalities
7		Tensile strength of coupling mechanism	At axial tensile force 300N No defects or abnormalities
8		Connection nut tightening torque	0.9~1.7N·m
	ENVIRONMENTAL		
9		Waterproof	IPX7 No water ingress inside the connector

	Remarks	Date
1		
2		
3		

Checked	Approved	Inspected	Prepared
三 22.08.30 村	山 22.08.30 本	檜 22.08.30 澤	渡邊 '22,08,30 直弘

GKQM-25